

save **ENERGY**, save the **NATION**



UP TO
80%
SAVING

LED Tri-proof Light

Model	JTL01-06-20W	JTL01-06-30W	JTL01-12-40W	JTL01-12-50W	JTL01-15-60W	JTL01-15-70W
Power	20W	30W	40W	50W	60W	70W
Luminous	2000lm-2200lm	3000lm-3300lm	4000lm-4400lm	5000lm-5500lm	6000lm-6600lm	7000lm-7700lm
Voltage	90-265 Vac 50/60Hz					
PF	> 0.95					
Colour Temperature	3000K / 4000K / 6000K					
Lm/W	100-110LM/W					
LED Source	SMD2835 EPISTAR CHIP					
CRI	> 80					
Life expectancy	50,000Hrs					
Beam Angle	120°					
Working Temperature	0 C to 40 C					
Compliance	LM80 / EMC / LVD / ROHS					
Product Size(mm)	L600*W91*H74	L600*W91*H74	L1200*W91*H74	L1200*W91*H74	L1500*W91*H74	L1500*W91*H74
Material	6063 Aluminum+PC					
Application	Supermarket / Exhibition hall / Parking place / Gas station / Tunnel / MTR station Etc Train station / Bus station / Airport / Factory / Warehouse					

Product & Specification are subject to change without prior notice.

* Product size is approximate and subject to change due to continuous development.

SHENZHEN GLAMLED TECHNOLOGY CO., LTD

Phone No. :+86 755 29362220 E-mail: info@glamled.com / Phoebe.H@glamled.com www.glamled.com